

SAILMAKERS INFORMATION SHEET

Model : Sabre 386

Revision # 2

6/14/2004

This information is for Selden Rigs only. See separate information sheet(s) for hulls with Hall Spar Rigs.

RIG SPECIFICATIONS

I: 51.83'

J: 15.00'

P: 45.33'

E: 16.50'

MAST SECTION

Hulls No. 217- 228, 233

Selden # 264 "C" SERIES

Hulls No. 229,230,231 and on with Selden rigs

Selden # 245 "C" SERIES

MAST SLIDERS

MDS Full batten car system for 5 full battens

Headboard assembly # 511-701-04

Batten Car (5) # 511-701-03

Intermediate Car (6) # 511-701-02

OPTIONAL FURLING MAST SECTION

Hulls No. 229 and on with Selden rigs

Selden # 246 "F" SERIES

BOOM SECTION

Selden # 200/117

REEFS

2 Slab reefs standard

Outhaul Slide # 511-570

NOTE FOR OPTIONAL SINGLE LINE REEFING BOOMS

MAXIMUM REEF HEIGHT IS LIMITED TO 13' 4.5"

FOR MAINSAIL TACK SET UP AND SET BACK INFORMATION SEE SELDEN "SAIL MAKER'S GUIDE"

AT: www.seldenmast.com

Click on the menu bar under "Manuals". Go to "General Information", then to "Sailmaker's guide"

(#595-542-E 2004-02-27)

NOTE: the dimensions for Sail entry "cut-back", Tack and Reef hook dimensions are slightly different between the two mast sections

HEADSTAY LENGTH

52' 9 1/2" (INCLUDES; extension link below furler),

for Furlex systems Link is 5 1/8" (# 517-062-01)

for Harken systems link is 6 7/8" (Johnson # 16-210)